



#### Input

- Nominal voltage: 230V<sub>AC</sub>, single phase
- Maximum line current per phase: 16A
- Load capacity: 3.7 kW
- Frequency: 50-60 Hz
- Plug type: IEC 60309 6H-P

#### Output:

- Nominal voltage: 230V<sub>AC</sub>
- Switched receptables: 20 x IEC C-13

#### Metering:

- Inlet: voltage, current, power
- Outlet: voltage, current, power

#### Rack Environment management:

- Optional temperature and humidity sensors (RJ-12 connector)

#### Control:

- 10-100 Mbps Ethernet (RJ-45 Connector)
- Authentifizierung: Active Directory®, LDAP, RADIUS
- Security: SSH, HTTPS, ACL, strong Passwords, Certificates, 256-bit AES encryption
- SMASH CLP, IPMI
- SNMP TRAPS, SETs, GETs, V2/V3
- Web-Browser access

#### Mechanical:

- Rack space: Zero U
- Mounting: Rack Mount brackets included
- Dimensions (WxDxH): 52,2 x 65,3 x 1539 mm
- Weight: 7.7lbs = 5,2 kg
- Display/panel: LED for current and voltage by outlet and total PDU
- Line cord: 4,5 m
- LED: power ON/OFF indicators at each outlet

#### Environmental requirements:

- Operating temperature: 5-45° Celsius
- Humidity: 5-90% RH non-condensing

#### Approvals:

- FCC Part 15, A; cTUVus, which is fully compliant with UL 60950-1 Rev. 3; EN 55022, Class A; EN 55024; EN 60950-1; CE mark; C-Tick and PSE, RoHS/WEEE compliant