



Input:

- Nominal voltage: 230V_{AC} single phase
- Maximum line current per Phase: 32A
- Rated current: 7.4 kW
- Frequency: 50-60 Hz
- Plug type: IEC 60309 6H-P

Output:

- Nominal voltage: 230V_{AC}
- Switched receptables: 20 x IEC C-13
- Overload protection: 2 x 16A UL489 circuit breaker

Metering:

- Inlet: current, voltage, power
- Outlet: current, voltage, power

Rack environment management:

- Optional temperature and humidity sensors (RJ-12 connector)

Control:

- 10-100 Mbps Ethernet (RJ-45 connector)
- Authentication: Active Directory®, LDAP, RADIUS
- Security: SSH, HTTPS, ACL, strong Passwords, certificates, 256-bit AES encryption
- SMASH CLP, IPMI
- SNMP TRAPS, SETs, GETs, V2/V3
- Web-Browser access

Mechanical:

- Rack space: Zero U
- Mounting: Rack Mount brackets included
- Dimensions (WxDxH): 52,2 x 65,3 x 1780 mm
- Weight: 11,3 lbs = 5,2 kg
- Display/panel: LED for current and voltage by outlet and total PDU
- Line cord: 15ft = 4,5 m
- LED: Power ON/OFF, indicators at each outlet

Environmental requirements:

- Operating temperature: 5-45° Celsius
- Humidity: 5-90% RH, non-condensing

Approvals:

- FCC Part 15, A; cTUVus, which is fully compliant with UL 60950-1 Rev. 3; EN 55022, Class A; EN 55024; EN 60950-1; CE; C-Tick and PSE
- RoHS/WEEE-compliant