



Input:

- Nominal voltage: 400V_{AC}, 3-phase WYE
- Maximum line current per phase: 16A
- Load capacity: 11 kW
- Frequency: 50-60 Hz
- Plug type: IEC 60309

Output:

- Nominal voltage: 230V_{AC}
- Maximum current draw per circuit: 16A
- Switch receptables: 12 x IEC C-19

Metering:

- Inlet: current, voltage and power for each line
- Outlet: current, voltage power for each outlet and total PDU

Control:

- 10-100 Mbps Ethernet (RJ-45 connector)
- Authentication: Active Directory®, LDAP, RADIUS
- Security: SSH, HTTPS, ACL, strong passwords, Certificates, 256-bit AES encryption
- SMASH CLP, IPMI
- SNMP TRAPS, SETs, GETs, V2/V3
- Web-Browser access

Mechanical:

- Rack space: Zero U
- Mounting: Rack Mount bracket included
- Dimensions (WxDxH): 52,2 x 65,3 x 1539 mm
- Weight: 12,3lbs = 5,6 kg
- Display Panel: : LED for PDU and outlet current and voltage
- Line cord: 10ft =3m
- LED: power ON/OFF at each output

Environmental requirements:

- Operating temperature: 5-45° Celsius
- Humidity: 5-90% RH, non-condensing

Approvals:

- FCC Part 15, A; UL and c-UL 60950
- RoHS-compliant

