



**Input:**

- Nominal voltage: 400V<sub>AC</sub>, 3-phase WYE
- Maximum line current per phase: 32A
- Load capacity: 22,2 kW
- Frequency: 50-60 Hz
- Plug type: IEC 60309

**Output:**

- Nominal voltage: 230V<sub>AC</sub>
- Maximum current draw per circuit: 6 x 16A
- Switched receptables: 18 x IEC C-13, 6 x IEC C-19
- Overload protection: UL489 circuit breaker

**Metering:**

- Inlet: Current, voltage and power for each line
- Outlet: Current, voltage, power at each outlet, phase and total PDU
- Current and power status (ON/OFF) for each circuit breaker

**Control:**

- 10-100 Mbps Ethernet (RJ-45 connector)
- Authentication: Active Directory®, LDAP, RADIUS
- Security: SSH, HTTPS, ACL, strong passwords, Certificates, 256-bit AES encryption
- SMASH CLP, IPMI
- SNMP TRAPS, SETs, GETs, V2/V3
- Web-Browser access

**Mechanical:**

- Rack space: Zero U
- Mounting: Rack Mount brackets included
- Dimensions (WxDxH): 52,2 x 65,3 x 1780 mm
- Weight: 10,8 kg
- Display Panel: LED for current and voltage by outlet and total PDU
- Line cord: 10ft = 3m
- LED: power ON/OFF indicators at each outlet

**Environment requirements:**

- Operating temperature: 5-45° Celsius
- Humidity: 5-90% RH non-condensing

**Approvals:**

- FCC Part 15 A: UL and c-UL 60950
- RoHS-compliant

400V 3Ø  
32A  
22kWVA