



Input:

- Nominal voltage: 230V_{AC}, single phase
- Maximum line current per phase: 16A
- Load capacity : 3,7 kW
- Frequency: 50-60 Hz
- Plug type: IEC 60309 6H-P

Output:

- Nominal voltage: 230V_{AC}
- Switchable receptables: 8 x IEC C-13

Metering:

- Inlet: current, voltage, power
- Outlet: current, voltage and power at each outlet and total PDU

Environment management:

- Operating temperature and humidity sensors (RJ-12 Connector)

Control:

- 10-100 Mbps Ethernet (RJ-45 connector)
- Authentication: Active Directory®, LDAP, RADIUS
- Security: SSH, HTTPS, ACL, strong passwords, certificates, 256-bit AES encryption
- SMASH CLP, IPMI
- SNMP TRAPS, SETs, GETs, V2/V3
- Web-Browser access

Mechanical:

- Rack space: 1U
- Mounting: Rack Mount brackets included
- Dimensions (WxDxH): 440 x 167 x 44 mm
- Weight: 3,6 kg
- Display/panel: LED for current and voltage by outlet and total PDU
- Line cord: 4,5 m
- LED: power (ON/OFF) at each outlet

Environment requirements:

- Operating temperature: 5-45° Celsius
- Humidity: 5-90% RH, non-condensing

Approvals:

- FCC Part 15, A; cTUVus, which is fully compliant with UL 60950-1 Rev. 3; EN 55022, Class A; EN 55024; EN 60950-1; CE; C-Tick and PSE
- RoHS/WEEE-compliant